



ISO 9001 Certified
Trusted Quality Since 1987

Cactus® Double Coated Foam Tape

Technical Data Sheet No. RP228

Product Information

Cactus® Double Coated Foam Tape RP228 is a differential tape with permanent adhesive on the open side and removable adhesive on the closed side. Permanent adhesive on the open side offer high tack and high adhesion for bonding a wide variety of substrates. Removable adhesive on the close side can be easily repositioned and removed cleanly without any residue.

Composition & Physical Properties

Adhesive System	: Solvent Rubber	Tape Thickness	: 1/32" (0.8 ± 0.1 mm)
Carrier	: Polyethylene Foam	Loop Tack FINAT-9	: Closed side 35.2±3.5 oz Open side >176.3 oz (5kg/25mm)
Foam Density	: 6 PCF	Peel Adhesion PSTC-101	: Closed side 28.2± 7 oz Open side >105.8 oz (3kg/25mm)
Liner Material	: SCK Paper	Shear Strength PSTC-7	: Over 24 hrs with 2.2 lbs loading on 1" x 1" (25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Thickness	: 3.1 mil	Service Temperature	: 32°F ~ 176°F (0°C ~ 80°C)
Liner Density	: #60 (90g/m ²)	Liner Color	: White
Tape Color	: White		

Applications

- Designed for temporary fixing and joining, clean removability from many surfaces such as nameplates, plastic trims, and posters.
- Great for POP displays, promotional and temporary signage, shelf talkers, exhibition and tradeshow displays.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.