



Product Information

Cactus® Double Coated Foam Tape RM228 is designed with removable rubber adhesive on both sides for easy repositioning and clean removal without any residue. It provides high tack and high shear strength adhesive and can securely bond to a wide variety of surfaces. The 6 PCF foam carrier provides high flexibility and conforms well to both smooth and uneven surfaces.

Composition & Physical Properties

| | | | |
|-----------------|-----------------------------|---------------------------|---|
| Adhesive System | : Removable Rubber | Tape Thickness | : 1/32" (0.8 ± 0.1 mm) |
| Carrier | : Polyethylene Foam | Loop Tack FINAT-9 | : 35.2 oz/in (1.0 ± 0.1 kg/25mm) |
| Foam Density | : 6 PCF | Peel Adhesion PSTC-101 | : 28.21 oz/in (0.8 ± 0.1 kg/25mm) |
| Liner Material | : SCK Paper | Shear Strength | : Over 24 hrs with 4.4 lbs loading on 1" x 1" (25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C) |
| Liner Thickness | : 3.1 mil | Service Temperature | : -4°F ~ 176°F (-20°C ~ 80°C) |
| Liner Density | : #60 (90g/m ²) | Liner Color | : White |
| Tape Color | : White | | |

Applications

- High shear strength adhesive can be used for mounting metal & plastic materials, great for both commercial or industrial uses.
- Designed for temporary indoor mounting & joining, clean removability from many surfaces such as nameplates, plastic trims, & posters.
- Fastening of metal or plastic articles, i.e. houseware, kitchenware, bathroom accessories, etc.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.