



Product Information

Cactus® Double Coated Film Tape A2920 - Differential acrylic (solvent based) PSA coated on both sides.
Open side: High grab system that provides quick bonding result on various substrates. Closed side: With a Semi-removable system that provides easy repositionability. Good resistance to weather, chemical and wide temperature range.

Composition & Physical Properties

Adhesive System	: Solvent Acrylic	Tape Thickness	: 2.5 mil (0.065 ± 0.005mm)	
Carrier	: 1/2 mil PET	Tack J. Dow No.	: Open Side 7	: Closed Side 18
Thickness	: 4.5 mil	Peel Adhesion PSTC-3	: 52.9 oz/inch (1.5kg/25mm)	: 10.6 oz/inch (0.3 ± 0.1 kg / 25 mm)
Liner Density/Material	: #74 (110 g/m ²) PE Coated Bleached Kraft Paper	Shear Strength PSTC-7	: Over 24 hrs	
Liner Color	: White	Heat Resistance	: Over 24 hrs with 17.6 oz loading on 1" x 1" (0.5 kg/25mm x 25mm) at 176°F (80°C)	
Tape Color	: Clear	Service Temperature	: -4°F ~ 212°F B23 (-20°C ~ 100°C)	: -22°F ~ 248°F (-30°C ~ 120°C)

Applications

- Exceptionally thin film tape for sticking metal or plastic parts that need excellent clear see-through appearance.
- Laminating of various substrates for easy kiss and die cutting process.
- Gasket and fastening applications in manufacturing or assembly of electronic parts and components

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.

