



Product Information

Cactus® Double Coated Tissue Tape L2450 is an acrylic solvent based adhesive tape that offers excellent tack and good shear strength for immediate bonding results. Highly suitable for splicing applications and resistant to solvents, heat and chemicals.

Composition & Physical Properties

| | | | |
|-----------------|------------------------------|----------------------------|--|
| Adhesive System | : Solvent Acrylic | Tape Thickness | : 4 mil (0.105 ± 0.005 mm) |
| Carrier | : Tissue | Loop Tack FINAT-9 | : 88↑ oz/inch (2.5 kg/25mm) |
| Liner Thickness | : 3 mil | Peel Adhesion PSTC-101 | : 63.4↑ oz/inch (1.8 kg/25mm) |
| Liner Material | : Glassine Paper | Shear Strength PSTC-107 | : Over 24 hrs with 35.2 oz loading on 1" x 1" (1.0 kg/25mm x 25mm) |
| Liner Density | : #60 (90 g/m ²) | Heat Resistance | : Over 24 hrs with 17.6 oz loading on 1" x 1" (0.5 kg/25mm x 25mm) at 176°F (80 °C) |
| Liner Color | : Mustard | Service Temperature | : -22°F ~ 284°F (-30°C ~ 140°C) short term |
| Tape Color | : White | | |

Applications

- Main applications: Splicing of industrial-grade plastic films, papers and foils, especially for applications where heating processes are involved and high temperature resistance of the adhesive tape is required
- Laminating and fastening for various industrial applications

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.