



Product Information

Cactus® Double Coated Foam Tape N221C is an acrylic solvent based adhesive tape that offers High -tack on both sides for quick stick and moderate shear strength for efficient operation. It's reinforced white 4 PCF cross-linked polyethylene flexible foam tape provide excellent adhesion to irregular and contour surfaces.

Composition & Physical Properties

Adhesive System	: Solvent Acrylic	Tape Thickness	: 39.37 mil (1.0 ± 0.1 mm)
Carrier	: Polyethylene Foam	Loop Tack	: J. Dow No. 16
Foam Density	: 4 PCF	Peel Adhesion	: PSTC-3 77.4 oz/in (2.2kg ± 0.1 kg/25mm)
Liner Material	: Glassine Paper	Shear Strength	: Over 24 hrs with 35.27 oz loading on 1" x 1" (1.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Thickness	: 3 mil	Service Temperature	: -4°F ~ 176°F (-20°C ~ 80°C)
Liner Density	: #60 (90 g/m ²)	Tape Color	: White
Liner Color	: White		

Applications

- Mounting & joining to nameplates, plastic trim, signs and emblems.
- Long-term bonding performance for mirror trim.
- Permanent fixing result for metal, wooden or plastic articles, e.g. houseware, kitchenware, bathroom accessories.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.