



Cactus® Double Coated Film Tape

Technical Data Sheet No. N297C

Product Information

Cactus® Double Coated Film Tape N297C is a solvent-based acrylic pressure sensitive adhesive tape which offers high initial tack and excellent shear strength for quick bonding results. Ideal for LSE substrates and other kinds of porous materials, and has high resistance to alkalization and low temperatures.

Composition & Physical Properties

Adhesive System	: Solvent Acrylic	Tape Thickness	: 3.9 mil (0.10 ± 0.01 mm)
Carrier	: 1/2 mil PET Film	Tack	: J. Dow No. 9
Liner Thickness	: 6 mil	Peel Adhesion	: PSTC-3 56.32 oz/inch (1.6kg/25mm)
Liner Material	: Bleached Kraft Paper	Shear Strength PSTC-7	: Over 24 hrs with 35.3 oz loading on 1" x 1" (1.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Density	: #80 (130 g/m ²)	Service Temperature	: -40°F ~ 212°F (-40°C ~ 100°C)
Liner Color	: White	Tape Color	: Clear

Applications

- For general purpose in industrial grade and for holding and mounting applications
- For heat breaking, gasketing and sealing of materials
- Excellent for laminating sailcloth seams and other seaming applications

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.

