## **Product Information**

Cactus® Double Coated Tissue Tape P247B is an acrylic solvent based adhesive tape that offers a high grab adhesive system that provides quick laminating results at a wide temperature range, chemical and UV resistance. Ideal as a splicing tape (passed industry-standard heat shear test)

## Composition & Physical Properties

Adhesive System : Solvent Acrylic	Tape Thickness	:	3.5 mil (0.09 ± 0.005 mm)
Carrier : Tissue	Loop Tack FINAT-9	:	84.6 oz/inch (2.4kg/25mm)
Liner Thickness : 4.7 mil	Peel Adhesion PSTC-101	:	49.38 oz/inch (1.4kg/25mm)
Liner Material : Bleached Kraft Paper	Shear Strength PSTC-7	:	Over 24 hrs with 35.2 oz loading on 1" x 1" (1.0kg/25mm x 25mm)
Liner Density : #74 (110 g/m²)	Heat Resistance	:	Over 24 hrs with 17.6 oz loading on 25mm x 25mm at 176°F (80°C)
Liner Color : White	Service Temperature	:	-40°F ~ 266°F (-40°C ~ 130°C) short term
Tape Color : White			

# **Applications**

- For general purpose bonding, fixing, mounting, & splicing ... etc. Industrial Grade.
- · Fastening for nameplate, trophy and sign.
- · Sticky grade for utility stationary, package market

### Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any direct or indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.

Copyright © 2019 V. Himark (USA) Inc., all rights reserved.

www.cactustape.com