



Product Information

Cactus® Double Coated Foam Tape Y221C is an acrylic solvent based adhesive tape that offers high shear strength and tack for secure bonding applications. It's reinforced with White 4 PCF cross-linked polyethylene foam tape allowing excellent adhesion to irregular and contour surfaces.

Composition & Physical Properties

Adhesive System	: Solvent Acrylic	Tape Thickness	: 39.37 mil (1.0 ± 0.1 mm)
Carrier	: Polyethylene Foam	Loop Tack	: FINAT-9 140.8 oz/in (4.0kg ± 0.1 kg/25mm)
Foam Density	: 4 PCF	Peel Adhesion	: PSTC-3 77.4 oz/in (2.2kg ± 0.1 kg/25mm)
Liner Material	: Glassine Paper	Shear Strength	: Over 24 hrs with 70.4 oz loading on 1" x 1" (2.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Thickness	: 3 mil	Service Temperature	: -4°F ~ 194°F (-20°C ~ 90°C)
Liner Density	: #60 (90 g/m ²)	Tape Color	: White
Liner Color	: Mustard		

Applications

- Mounting & joining to nameplates, plastic trim, signs and emblems.
- Long-term bonding performance to mirror trim.
- Permanent fixing result for metal, wooden or plastic articles, e.g. houseware, kitchenware, bathroom accessories.
- Window glazing.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.