

PRODUCT INFORMATION

CACTUS

NO. L293

Double-coated adhesive tape



Features/characteristics

1. Adhesive : Acrylic (solvent based) adhesive coated on both sides.
2. Carrier : 9 μ transparent PET film.
3. Liner : 90 g/m² glassine release liner, mustard color.
4. Super thin tape that adheres to smooth surface with superior transparency, effective for fastening in tight spaces.
5. High grab tack system that provides quick bonding result with good temperature, chemical and UV resistance.

Technical data

1. Thickness : 0.03 mm (+ 0.003 / - 0 mm)
2. Loop Tack : FINAT-9 1.2 kg / 25 mm
3. Peel Adhesion : PSTC-3 0.9 \pm 0.1 kg / 25 mm
4. Shear Strength : PSTC-7 Over 72 hrs with 1.0 kg loading on 25 mm x 25 mm
5. Heat Resistance : Over 24 hrs with 0.5 kg loading on 25 mm x 25 mm at 80°C
6. Service Temperature : -20°C ~ 120°C

Applications

1. Flexible tape for fastening to metal plates, film and plastic parts with high conformity, especially where high transparency is a requirement.
2. Fixing and laminating of various substrates of electronic components and devices.

Remark

All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty. It's essential that the user should evaluate the product for a period of time to determine whether it is fit for a particular purpose and suitable for the user's method of application.

2009/6/18